



KORTON INDUSTRIAL LIMITED



7.48 Inch | 190 Millimeter x 13.386 Inch | 340 Millimeter x 2.165 Inch | 55 Millimeter NTN NUP238EG1C3 Cylindrical Roller Bearings

Bearing No. NUP238EG1C3

NUP238EG1C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	18.417
EAN	4547359135756
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring with Side Plate 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	190MM Bore; Straight Bore Profile; 340MM Outside



KORTON INDUSTRIAL LIMITED

	Diameter; 55MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Reta
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	NUP238EG1C3
Weight / LBS	46.958
B	2.165 Inch 55 Millimeter
d	7.48 Inch 190 Millimeter
D	13.386 Inch 340 Millimeter
bore diameter:	190 mm
precision rating:	ISO Class 0
outside diameter:	340 mm
maximum rpm:	2000 rpm
overall width:	55 mm
bearing material:	Hardened Alloy Steel
flanges:	(2) Outer Ring, (2) Inner Ring
cage material:	High Strength Machined Brass Rivetless w/ square holes
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	55 mm
ring separation:	Separable Inner Ring



KORTON INDUSTRIAL LIMITED

fillet radius:	4 mm
operating temperature range:	-40 to 120 ° C
series:	NUP
dynamic load capacity:	695000 N
manufacturer product page:	Click here
static load capacity:	955000 N